

**VRLA / SLA Battery series** is designed with AGM Long life / Duration In High Performance Plate with Gain Extra Powder in Purify Electrolyte. Innovation Design of Fully Maintenance Free in Float Life 12 years. This is Highly Suited to Backup Applications in UPS/EPS, Security Alarm System, Deep Cycle Applications use in Telecom System and Solar System.

**Feature**

- Smart UPS Battery Design up to 15%
- Battery Capacity 65Ah / 1100W - 15min
- AGM/SLA - Seal Lead Acid Battery
- Maintenance Free Battery Operation
- Non-Spillable Construction Design
- ABS container & Cover UL94HB-0
- Safety Value in Explosion proof
- CE & UL Product Certification
- ISO9001 & ISO14001 Certified Factory

**Application**


- UPS & EPS
- Emergency System
- Communication Eq.
- Control Equipment
- Solar System
- Alarm System
- Medical Equipment
- Cable TV & CCTV
- Solar System




**Specifications**

Voltage Normal	: 12 VDC	in 6 Cell
Capacity @20Hr	: 69Ah	@3.44A/ 41.3W
@ 5Hr	: 60Ah	@12.1A/ 138W
@ 1Hr	: 42Ah	@42.3A/ 473W
@15min	: 25Ah	@101 A/ 1110W (*UPS)
@ 5min	: 14Ah	@173 A/ 1854W (*UPS)
Max. Discharge	: 900A	@14C
Max. Charge Current	: 20A	@0.3C
Internal Resistance	: Apporx. 6 mΩ	Full Charge at 25°C
Design Float Life	: 12 years	at 25 °C
Cycle Lift Service	: 1500 cycles	at DOD 25%
Float Charge Voltage	: 13.5-13.8V	(-20mV/°C) at 25°C
Cycle Charge Voltage	: 14.4-15.0V	(-30mV/°C) at 25°C
Operation Temp.	: Normal	25+ / -3 °C
	: Discharge	-15 – 50 °C
	: Charge	-15 – 50 °C
	: Storage	-15 – 50 °C
Self Discharge	: more than 6 Month	at 25°C
Terminal	: M6	
Container Material	: ABS UL94 HB-0	(Option :UL94V-0)
Physical	: 350x166x179mm	– 21.2 Kgs


**Dimension 350x166x179mm Weight = 21.2kgs @M6**




**Terminal Voltage (V) and Discharge Time**




Battery Voltage and Charge Time for Standby Use



Battery Voltage and Charge Time for Cycle Use



Cycle Service Life



**Constant Current(Amp) and Power (Watt/Box) Discharge Table**

CHU.BRO-04.BAT.UB1265-1100W.Rev1.00/2020

**VRLA-Battery Performance : %DOD, Constant Current, Constant Power (25°C / 10.2 F.V.)**

Discharge Time	5 Min	10Min	15Min	20Min	30Min	60Min	2Hr	3Hr	5Hr	10Hr	20Hr
%DOD	22%	32%	39%	42%	49%	65%	70%	81%	93%	100%	106%
Cons. Current	173A	127A	101A	82A	63.7A	42.3A	22.7A	17.6A	12.1A	6.51A	3.44A
Cons. Power	1854W	1396W	1110W	902W	720W	473W	261W	201W	138W	78W	41.3W